


3235084-SE-4005

PLAN

- 1. REFER TO DRAWING SE-4005 FOR NOTES.
- 2. THE LEVEL AND CONTINUITY OF THE TOP OF SLIGHTLY WEATHERED TO UNWEATHERED ROCK IS INFERRED BASED ON OBSERVATIONS AND THE RESULTS OF TESTING AT DISCRETE LOCATIONS NEAR BUT OFF THE ALIGNMENT OF THE NEW BRIDGE STRUCTURE. AS SUCH, THE ACTUAL ROCK LEVELS ACROSS THE BRIDGE SITE MAY VARY FROM WHAT IS SHOWN ON THIS DRAWING.
- 1225 SUPER TEE GIRDERS REFERRED TO HEREIN ADOPTS A SLIGHTLY MODIFIED GIRDER GEOMETRY TO THAT OF THE STANDARD NZTA WAKA KOTAHI 1225 STANDARD SUPER TEE DRAWINGS.
- 4. SLOPE STABILITY PILES TO BE INSTALLED PRIOR TO COMMENCING



T.ZHU

Dwg Check D.SHINNICK 19.01.22 Da

19.01.22

WAKA KOTAHI

SH16 - SAFETY IMPROVEMENTS

STAGE 2

BRIGHAM CREEK TO KUMEU

D ISSUED FOR DRAFT DETAILED DESIGN / FOR CONSENTING

III Beca

C PEER REVIEW 30% DESIGN

A PRELIMINARY DESIGN

B ISSUED FOR DRAFT DETAILED DESIGN

NOT FOR CONSTRUCTION


STRUCTURAL ENGINEERING

3235084-SE-4006

KUMEU SHARED USE BRIDGE

GENERAL ARRANGEMENT

LONG SECTION



BRIGHAM CREEK TO KUMEU

CROSS SECTIONS

Dwg Check D.SHINNICK 19.01.22 Dal

A PRELIMINARY DESIGN

3235084-SE-4007

PLAN 1:100 (A1), 1:200 (A3)

UP STREAM

D ISSUED FOR DRAFT DETAILED DESIGN / FOR CONSENTING C PEER REVIEW 30% DEISIGN **Beca** B ISSUED FOR DRAFT DETAILED DESIGN A PRELIMINARY DESIGN

PIPE AND OUTLET

T.ZHU 19.01.22 Dwg Check D.SHINNICK 19.01.22 Da

HOLD

WAKA KOTAHI

HOLD

SH16 - SAFETY IMPROVEMENTS STAGE 2 BRIGHAM CREEK TO KUMEU


BRIGHAM CREEK SHARED USE BRIDGE GENERAL ARRANGEMENT - PLAN

NOT FOR CONSTRUCTION STRUCTURAL ENGINEERING 3235084-SE-4105

ORIGINAL DRAWING


IN COLOUR


DETAILED DESIGN





1. REFER TO DRAWING SE-4105 FOR NOTES.





ORIGINAL DRAWING
IN COLOUR

DETAILED DESIGN
NOT FOR CONSTRUCTION

Despire
Osciple


Beca

 Original Scale (A1)
 Design
 J.CHEN
 19.01.22 (Drawn
 Approved For Obselvation*

 1.100
 T.2HU
 19.01.22 (Drawn
 Design T.2HU
 Document
 Design T.2HU
 Document
 Design T.2HU
 Document
 Design T.2HU
 Design T.2HU
 Document
 Design T.2HU
 Design T.2


WAKA KOTAHI NZ TRANSPORT AGENCY SH16 - SAFETY IMPROVEMENTS STAGE 2 BRIGHAM CREEK TO KUMEU BRIGHAM CREEK SHARED USE BRIDGE G.A. - CROSS SECTIONS | Discipline | STRUCTURAL ENGINEERING | DISCipline | DISC


- 1. REFER TO DRAWING SE-4105 FOR NOTES.
- 2. REFER TO DRG SE-4030 FOR SERVICES SUPPORT DETAILS.
- 3. REFER TO CIVIL PACKAGE FOR IN GROUND SERVICE TRENCH



A SECTION - WEST ABUTMENT
[\$E-4107] 1:25 (A1), 1:50 (A3)

BACKWALL





C SECTION - TYPICAL DECK SE-4107 1:25 (A1), 1:50 (A3)

Traving Originator:

The Beca

| Original | Design | J.CHEN | 19.01.22 | Approved For | 12.5 | Reduced (A3) | Design | J.CHEN | 19.01.22 | Construction* | Day Verifier | Day Verifier | Day Check | D.SHINNICK | 19.01.22 | Date | D

WAKA KOTAHI NZ TRANSPORT AGENCY SH16 - SAFETY IMPROVEMENTS STAGE 2 BRIGHAM CREEK TO KUMEU


BRIGHAM CREEK SHARED USE BRIDGE DETAILED CROSS SECTIONS

NOT FOR CONSTRUCTION

Discipline
STRUCTURAL ENGINEERING
Drawing No.
3235084-SE-4108
D

DETAILED DESIGN

ORIGINAL DRAWING
IN COLOUR







SH16 - SAFETY IMPROVEMENTS STAGE 2 BRIGHAM CREEK TO KUMEU BRIGHAM CREEK
BARRIER BEAM
GENERAL ARRANGEMENT - PLAN

Discipline
STRUCTURAL ENGINEERING
Drawing No.
3235084-SE-4205
C

DETAILED DESIGN

1. REFER TO DRAWING SE-4205 FOR NOTES.


EXCAVATION WORKS.

 THE LEVEL AND CONTINUITY OF THE TOP OF SLIGHTLY
 WEATHERED TO UNWEATHERED ROCK IS INFERRED BASED ON OBSERVATIONS AND THE RESULTS OF TESTING AT DISCRETE LOCATIONS NEAR BUT OFF THE ALIGNMENT OF THE NEW

3. SERVICES ARE NOT SHOWN ON THESE DRAWINGS FOR CLARITY. CONTRACTOR SHALL CONFIRM THERE IS NO DIRECT CONFLICT WITH THE UNDERGROUND SERVICES AND IMPLEMENT APPROPRIATE PROTECTION MEASURES PRIOR TO CARRYING OUT


4. REFER TO DESIGN REPORT FOR HISTORICAL DRAWINGS.

STRUCTURES. AS SUCH, THE ACTUAL ROCK LEVELS ACROSS THE SITE MAY VARY FROM THOSE SHOWN ON THIS DRAWING.



ELEVATION - SOUTHERN BARRIER BEAM

1:100 (A1), 1:200 (A3)



C ISSUED FOR DRAFT DETAILED DESIGN / FOR CONSENTING

B PEER REVIEW 30% DEISIGN

A ISSUED FOR DRAFT DETAILED DESIGN

III Beca

T. Zhu 19.01.22 Dwg Check D.SHINNICK 19.01.22 Dal


* COS

WAKA KOTAHI


SH16 - SAFETY IMPROVEMENTS STAGE 2 BRIGHAM CREEK TO KUMEU


BRIGHAM CREEK BARRIER BEAM - GENERAL ARRANGEMENT - LONG SECTION

ORIGINAL DRAWING IN COLOUR **DETAILED DESIGN**



1. REFER TO DRAWING SE - 4205 FOR NOTES.





SECTION - CULVERT CENTRELINE 1:100 (A1), 1:200 (A3)

C ISSUED FOR DRAFT DETAILED DESIGN / FOR CONSENTING B PEER REVIEW 30% DEISIGN A ISSUED FOR DRAFT DETAILED DESIGN No. Revision	3 PN TC GC 26.08.22 TZ DS GC 23.03.22 TZ DS GC 19.01.22 By Crik Appd Date	III Beca	Design D.Shinnick 19.01.22 Agroroed For	Client: WAKA KOTAHI NZ TRANSPORT AGENCY	Project: SH16 - SAFETY IMPROVEMENTS STAGE 2 BRIGHAM CREEK TO KUMEU	BRIGHAM CREEK BARRIER BEAM - GENERAL ARRANGEMENT - CROSS SECTION

STRUCTURAL ENGINEERING 3235084-SE-4207

ORIGINAL DRAWING IN COLOUR

DETAILED DESIGN NOT FOR CONSTRUCTION


1. GENERAL 1.1 REFER TO DWG SE-4205 FOR NOTES.


- 1.2 ALL FORMED SURFACE TO BE F4 FINISH, EXCEPT WHERE NOT VISIBLE TO PUBLIC F3 ACCEPTABLE.
- 1.3 ALLOW FOR 20mm CHAMFER TO ALL CONCRETE EDGES U.N.O.
- ALL CONSTRUCTION JOINTS TO BE TYPE 'B' U.N.O.
- REFER TO DWG SE-4220 FOR STRESS BAR DETAILS
- REFER TO DWG SE-4227 FOR PRECAST BEAM DETAILS
- 1.7 REFER TO DWG SE-4240 FOR CONSTRUCTION SEQUENCE.

- 2. EXCAVATION
 2.1 THE CONTRACTOR SHALL PROVIDE A STABLE EXCAVATION FOR CONSTRUCTING BARRIER BEAM.
- 2.2 THE EXISTING CULVERT IS ASSUMED TO BE SURROUNDED BY WELL COMPACTED GRANULAR FILL. THE COMPOSITION OF THE EXISTING FILL SHALL BE CONFIRMED ON SITE BY GEOTECHNICAL ENGINEER BY VISUAL INSPECTION.
- 2.3 THE CONTRACTOR SHALL TAKE PRECAUTIONS TO PREVENT OVER DIG OR DAMAGE TO THE EXISTING CULVERT WHEN EXCAVATING TO FORMATION I EVEL
- A 75mm CLEAR GAP BETWEEN THE PRECAST BEAM DEFLECTED SOFFIT LEVEL AND GROUND LEVEL SHALL BE MAINTAINED UNTIL AFTER THE SECOND CONCRETE POUR AND THE CONCRETE REACHES 28 DAY STRENGTH

3. BACKFILL

- FLOWABLE FILL IN ACCORDANCE WITH AS/NZS 2041.2 AND THE EARTHWORKS SPECIFICATION SHALL BE POURED AFTER THE SECOND INSITU CONCRETE POUR REACHES 28 DAY STRENGTH ALLOWING THE BEAM TO DEFLECT UNDER ITS OWN DEAD WEIGHT, FILLING THE GAP BETWEEN THE BEAM SOFFIT AND EXISTING GROUND LEVEL.
- BACKFILLING AND COMPACTION TO THE VERTICAL FACE OF THE BARRIER BEAM SHALL BE CARRIED OUT AFTER THE BEAM'S SECOND CONCRETE POUR ACHIEVE ITS MINIMUM 28 DAY
- BACKFILL SHALL COMPRISE OF GAP65 HARDFILL U.N.O. AND SHALL BE BUILT UP IN LONGITUDINAL LAYERS OVER THE HEIGHT OF THE BARRIER BEAM ON BOTH SIDES OF THE CARRIAGEWAY SIMULTANEOUSLY.
- 3.4 ALL CONSTRUCTION PLANT AND OTHER VEHICLES HAVING A MASS OF 1500KG SHALL BE KEPT 3m AWAY FROM THE BACK OF THE WALLS.
- COMPACTION OF BACKFILL WITHIN A HEIGHT OF 1.5m ABOVE THE ARCH CULVERT SHALL BE HAND COMPACTED IN ACCORDANCE WITH WAKA KOTAHI F3 "SPECIFICATION FOR PIPE CULVERT CONSTRUCTION". HAND COMPACTION IS ASSUMED TO BE VIBRO TAMPERS HAVING A MASS NOT EXCEEDING 75KG.
- THE PLANT USED FOR COMPACTING FILL MATERIAL OUTSIDE THE 1.5m ZONE INDICATED IN NOTE 3.5 SHALL BE RESTRICTED TO:
- VIBRATING ROLLERS, HAVING A MASS PER METRE WIDTH OF ROLLER NOT EXCEEDING 1300KG WITH A TOTAL MASS NOT
- VIBRATING PLATE COMPACTOR HAVING A, MASS NOT EXCEEDING 100KG.
- VIBRO TAMPERS HAVING A MASS NOT EXCEEDING 75KG.
- CONTRACTOR SHALL PROVIDE BENCHING TO INTERFACE OF THE BACKFILL WITH THE EXISTING GROUND SUCH THAT THE FILL IS KEYED IN. THE CONTRACTOR SHALL CONSTRUCT BENCHING AS THE FILL IS RAISED SUCH THAT THE REQUIRED COMPACTION OF THE FILL MATERIAL /KEYING IN AT THE INTERFACE IS ACHIEVED. THE BENCH HEIGHT SHALL BE BASED ON THE THICKNESS OF MATERIAL PLACED IN EACH LIFT BUT SHALL BE NO GREATER THAN 500mm HIGH TOPSOIL AND UNSUITABLE MATERIAL SHALL BE TRIMMED PRIOR TO ANY FILLING











ORIGINAL DRAWING IN COLOUR DETAILED DESIGN NOT FOR CONSTRUCTION

C ISSUED FOR DRAFT DETAILED DESIGN / FOR CONSENTING B PEER REVIEW 30% DEISIGN A ISSUED FOR DRAFT DETAILED DESIGN

Beca

T. Zhu 19.01.22 Dwg Check D.SHINNICK 19.01.22 Da

*COS

WAKA KOTAHI

NORTHERN KERB.

FOR PAVEMENT DETAILS

FLOWABLE FILL

PRECAST BEAM

REFER TO SE-4227

2 LAYER OF 1000 GAUGE

POLYTHENE SHEETING

REFER TO NOTE 3.1

REFER TO CIVIL DRAWINGS

DRAWINGS FOR DETAILS

REFER TO CIVIL

SH16 - SAFETY IMPROVEMENTS STAGE 2 BRIGHAM CREEK TO KUMEU

- IN-SITU POUR

999

REFER TO SE-4220

REFER TO CIVIL PACKAGE FOR NEW SERVICES

FINISHED GROUND

REGRADED SLOPE

PROFILE

3.7

BRIGHAM CREEK BARRIER BEAM **DETAILED CROSS SECTIONS** STRUCTURAL ENGINEERING 3235084-SE-4208